

28-Port Gigabit Managed Switch



Product Highlights

- Supports 24*1G RJ45 ports, 4 *1G SFP ports, and 1* Console port
- Supports IEEE802.3/IEEE802.3i/IEEE802.3u/IEEE802.3ab/IEEE802.3z, storage and forwarding
- RJ45 port supports 10M/100M/1G adaptation
- Adopting a storage and forwarding exchange mechanism
- The panel indicator LEDs will monitor the working status and assist in fault analysis
- Supports 802.1x port authentication, AAA authentication, and TACACS+ authentication
- Support WEB, TELNET, CLI, SSH, SNMP, RMON management

Hardware Features

Description	Specification
Model	HR-SWG20244S
Interface	24* 1G RJ45 ports 4 *1G SFP ports 1* Console port
Port Standard	IEEE802.3 (Ethernet) IEEE802.3u (Fast Ethernet) IEEE 802.3ab (Gigabit Ethernet) IEEE 802.3z (Gigabit Ethernet Fiber Standard) IEEE802.3x (Flow Control) IEEE 802.3az (Efficient and Energy saving Ethernet) IEEE 802.3ad (Link Aggregation) IEEE 802.1AB LLDP/LLDP MED (Link Layer Discovery Protocol) IEEE 802.1D Spanning Tree Protocol IEEE 802.1w Rapid Spanning Tree Protocol IEEE 802.1s Multiple Spanning Tree Protocol (Fast Spanning Tree) IEEE 802.1Q (Virtual Local Area Network) IEEE 802.1p (VLAN Tag) IEEE 802.1X (User Authentication)
Bandwidth	56Gbps
Packet Forwarding Rate	41.66Mpps
Packet Buffer	4.1Mbit
MAC Address Table	8K
Jumbo Frame	10K
VLAN	VLAN range 1-4094, maximum active VLAN is 256
Transmission Method	Store and Forward
Power Supply	AC 100-240V 50/60Hz DC 12V 3A

Hardware Features

Description	Specification
Mainboard Power Consumption	20.79W
Structure Information	Product Dimensions :440*204*44mm Packaging Dimensions : 500*290*85mm Product Net Weight: 2.45kg Product Gross Weight:3.06kg
Packing Information	Carton Dimensions :520*445*310mm Packing Quantity: 5PCS Packing Weight: 16.3KG
Package Contents	Switch 1pcs, power cord 1pcs,manual 1pcs,certificate of qualification 1pcs
Fan Quantity	0
Installation	Desktop,rack-mounting
Surge Protection	Port Surge: Common mode 4KV, differential mode 2KV ; Electrostatic ESD: Air 8KV, Contact 6KV
Operating Temperature	0~40℃
Storage Temperature	-40 ℃ to 70 ℃
Operation Humidity	10%~90%,non condensing
Storage Humidity	5%~95%,non condensing
PWR Green LED	On: Powered on Off: Powered off
SYS Green LED	Flashing: System startup in progress On: The system is running normally
Link Green LED	On: Link normal Off: Link blocked
ACT Green LED	On: Data transmitting Off: No Data transmitting
Reset	Long press for 6 seconds to restore factory settings

Software Features

Description	Specification
L2+ Function	
IPv4	IPv4 VLAN Interface
	IPv4 Static Routes
	ARP
IPv6	IPv6 VLAN Interface
	IPv6 Static Routes
	IPv6 ND
L2 Function	
Port	Port Switch configuration
	Port Description configuration
	Port Speed configuration
	Port Duplex configuration
	Port Flow Control configuration
	Jumbo Frame
	EEE
	Fiber Module(DDM)
Link Aggregation	Supports load balance policy; Base on MAC and IP-MAC
Storm Control	Boardcast suppression
	Unknown Multicast
	Unknown Unicast
Port Mirroring	One to one monitor
	Many to one monitor
	Ingress/Egress/Both
	Up to 4 session groups
Port Security	MAC Address Constraints
	Port Security MAC Address
	Protect/Restrict/Shutdown
Port Isolation	Support
Port Rate-limit	Support
Loopback Detection	Support

Software Features

Description	Specification
VLAN	Access/Trunk/Hybrid
	VLAN Tunnel (Q-in-Q Tunnel)
	VLAN range 1-4094, maximum active VLAN is 256
	Voice VLAN
	MAC VLAN
	Surveillance VLAN
	Protocol VLAN
MAC Address	GVRP
	Dynamic MAC address
	Static MAC address
Spanning Tree Protocol	Filtering MAC Address
	STP/RSTP/MSTP
	BPDU Filter
	BPDU Guard
LLDP	Edge Port
	LLDP
	LLDP MED
Multicast	IGMP Snooping
	IGMP V1/V2/V3
	Router Port
	Static IGMP group address
	IGMP groups filtering
	Querier
	MLD Snooping
	MVR
	Traffic classification based, Strict priority and WRR
QoS	Port Priority
	802.1P Priority
	IP TOS Priority
	IP DSCP Priority

Software Features

Description	Specification
ERPS	Only SFP port
Services	
	DHCP Server
	IP Pool
DHCP	Static Binding
	Port Static Binding
	DHCP Relay
	HTTP
	HTTPS
	Telnet
	SSHv2
Access Protocol	Manager ACL
	Session Timeout
	Password Retry Count
	Silent Time
Security	
	RADIUS
	TACACS+
AAA	802.1X
	Base on port/MAC/local/WEB
	Global/VLAN
DHCP Snooping	Option 82
	Circuit ID

Software Features

Description	Specification
IP Source Guard	Support
Dynamic ARP Inspection	Support
DoS	Support
ACL	MAC ACL
	IPv4 ACL
	IPv6 ACL
Diagnostics	
Syslog	Logging Message
	Remote Server
Ping	Support
Traceroute	Support
Copper Test	Support
UDLD	Support
Port Statistics	Support
Equipment Management	
Manager Access	Console
	HTTP/HTTPS
	Telnet
	SSH
	SNMP
Manager IP	Static Address
	DHCP Client
	Supports IPv4 and IPv6 address
	Manager VLAN
	DNS
Time Synchronization	SNTP
	Manual Time
SNMP	V1/V2C/V3
	Community
	V3 User
	Group
	Trap Host

Software Features

Description	Specification
SNMP MIB	RFC 1213 MIB-II
	RFC 1493 Bridge MIB
	RFC 1643 Ethernet MIB
	RFC 2819 RMON MIB (Groups 1, 2, 3 and 9)
	RFC 2863 Interface MIB
	LLDP
RMON	Private MIB
	Statistics
	History Configuration
	Event Configuration
User Management	Alarm Configuration
	Support
	Firmware upgrade
	Upload and download
Firmware Management	
Configuration Management	
Save	Support
Restart	Support
Factory Defaults	Support
Standard Compliance	
IEEE 802.3x flow control and back pressure	
IEEE 802.3ad port trunk with LACP	
IEEE 802.1D Spanning Tree Protocol	
IEEE 802.1w Rapid Spanning Tree Protocol	
IEEE 802.1s Multiple Spanning Tree Protocol	
IEEE 802.1p Class of Service	
IEEE 802.1Q VLAN tagging	
IEEE 802.1x Port Authentication Network Control	
IEEE 802.1ab LLDP	
RFC 768 UDP	
RFC 793 TFTP	
RFC 791 IP	

Software Features

Description	Specification
RFC 792 ICMP	
RFC 2068 HTTP	
RFC 1112 IGMP v1	
RFC 2236 IGMP v2	
RFC 3376 IGMP v3	
RFC 2710 MLD v1	
FRC 3810 MLD v2	

Product Structure Diagram

