

DS-PDP15P-EG2-WB

DS-PDP15P-EG2-WB is a fully supervised two-way wireless detector featuring motion detection, tamper protection, low battery and supervision. It can operate for up to 5 years from an in-built battery, and monitors the area within 15 m radius, ignores animals while recognizing human from the first step.

- Detection Range: 15m / 85.9°
- Up to 30KG pet immunity
- SEC (Smart Environmental Control) - Advanced digital signal processing and 3D optics
- Fully remote configurable through App
- Multiple enrollment method and easy installation design
- Easy replaceable battery with PCB protected
- Frequency hopping against jamming for reliable transmission

▪ Specification

Detection Performance	
Detection Method	Passive Infrared
Detection Range	15m
Detection Angle	85.9°
Detection Zones	52
Detectable Speed	0.3 ~ 2m/s
Sensitivity	Auto,High,Pet
Pet Immunity	30Kg
White Light Filter	6500lux
Digital Temperature Compensation	Support
Creep Zone Protection	Support
Feature	
Digital Processing	Support
Sealed Optics	Support
Tamper Protection	Front,Rear
Environment Temperature Indicator	Support
Signal Strength Indicator	Support
Interface	
Power Switch	Power Up Enrolling
LED Indicator	Blue(Alarm)
Transmission	
Transmission Technology	Tri-X Wireless
Transmission Method	Two-Way RF Wireless
Transmission Frequency	433MHz
Transmission Security	AES-128 Encryption
Transmission Range(Free Space)	1.2Km
Frequency Hopping	Support
Enrolling Method	Power up,Remote ID,QR Code
Electrical Characteristics	
Standard Battery Life	Up to 5 years (standby time)
Power Supply	Battery Powered
Battery Type	CR123A × 1
Typical Voltage	3V
General	
Operation Temperature	-10 °C to 55 °C (14 °F to 131 °F)
Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Operation Humidity	10% to 90%
Dimension(WxHxD)	65.5mm × 103mm × 48.5mm
Weight	128g
Mounting Height	1.8 to 2.4m

Mounting Method	Wall
Application Scenario	Indoor
Bracket	Optional Wall & Ceiling Accessory

▪ Available Model

DS-PDP15P-EG2-WB

▪ Accessory

▪ Optional

DS-PWA96-Kit-WB/ 12V	DS-PDB-IN-Ceiling bracket Internal wall mounted bracket	DS-PDB-IN-Wall bracket Internal ceiling mounted bracket	DS-PDP-IN-CR123A Indoor Detector Battery
			

Headquarters

No.556 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T: +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



HIKVISION



HIKVISIONHQ



HIKVISIONHQ



HIKVISION_Global



HIKVISION
Corporate Channel



hikvisionhq