

DS-PS1-E-WB Wireless External Sounder



- 433 MHz two-way wireless communication
- 3 years battery life span (triggered every two weeks and alerting 90 s for each triggering)
- AES-128 encryption
- Front and rear panel tamper-proof
- 3 kinds of alarm sounds: fire alarm, panic alarm, and intrusion alarm
- Buzzer Decibel: 110 dB
- Fully remote configurable through App
- Multiple enrollment methods and easy installation design
- Frequency hopping against jamming for reliable transmission
- IP65 protective level

▪ Specification

Electrical characteristics	
Battery type	Battery (default power supply method) or 12 VDC
Power supply	Battery (default power supply method) or 12 VDC
Operation humidity	10% to 90% (no condensing)
Operation temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Battery life span	Up to 3 years (standby time)
Wireless transmission	
RF frequency	433 MHz
RF modulation	2GFSK
RF distance	900 m (open area)
General	
IP rate	IP65
Installation method	Wall mounting
Dimension(WxHxD)	190 × 200 × 47.3 mm(7.48" × 7.87" × 1.86")
Shell material	PC+ABS
Weight	606.5 g (21.4 oz)

▪ Available Model

DS-PS1-E-WB

Headquarters

No.556 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T: +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



HIKVISION



HIKVISIONHQ



HIKVISIONHQ



HIKVISION_Global



HIKVISION
Corporate Channel



hikvisionhq