

## DS-2CD2625FWD-IZS 2 MP IR Varifocal Bullet Network Camera



### Key Features

- 1/2.8" Progressive Scan CMOS
- 1920 × 1080 @30fps
- Powered by Darkfighter
- H.265, H.265+
- 120dB WDR
- IP66, IK10
- IR range: up to 50 m
- BLC/3D DNR/ROI/HLC
- Smart encoding: Support low bit rate, low latency
- 4 behavior analyses and face detection
- Color: 0.005 Lux @ (F1.2, AGC ON), 0 Lux with IR  
Color: 0.0068 Lux @ (F1.4, AGC ON), 0 Lux with IR



## Specifications

| <b>Camera</b>               |                                                                                                                                                                                                     |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Image Sensor                | 1/2.8" Progressive Scan CMOS                                                                                                                                                                        |
| Min. Illumination           | Color: 0.005 Lux @ (F1.2, AGC ON), 0 Lux with IR<br>Color: 0.0068 Lux @ (F1.4, AGC ON), 0 Lux with IR                                                                                               |
| Shutter Speed               | 1/3 s to 1/100,000 s                                                                                                                                                                                |
| Slow Shutter                | Yes                                                                                                                                                                                                 |
| Day & Night                 | IR Cut Filter                                                                                                                                                                                       |
| Digital Noise Reduction     | 3D DNR                                                                                                                                                                                              |
| WDR                         | 120dB                                                                                                                                                                                               |
| 3-Axis Adjustment           | Pan: 0° to 360°, tilt: 0° to 90°, rotate: 0° to 360°                                                                                                                                                |
| <b>Lens</b>                 |                                                                                                                                                                                                     |
| Focal length                | 2.8 to 12 mm                                                                                                                                                                                        |
| Lens Type                   | Motorized                                                                                                                                                                                           |
| Aperture                    | F1.4                                                                                                                                                                                                |
| Focus                       | Auto                                                                                                                                                                                                |
| FOV                         | Horizontal field of view: 105° to 35°<br>Vertical field of view: 56° to 20°<br>Diagonal field of view: 126° to 40.5°                                                                                |
| Lens Mount                  | Ø14                                                                                                                                                                                                 |
| <b>IR</b>                   |                                                                                                                                                                                                     |
| IR Range                    | Up to 50 m                                                                                                                                                                                          |
| Wavelength                  | 850nm                                                                                                                                                                                               |
| <b>Compression Standard</b> |                                                                                                                                                                                                     |
| Video Compression           | Main stream: H.265/H.264<br>Sub stream: H.265/H.264/MJPEG<br>Third stream: H.265/H.264                                                                                                              |
| H.264 Type                  | Main Profile/High Profile                                                                                                                                                                           |
| H.264+                      | Main stream supports                                                                                                                                                                                |
| H.265 Type                  | Main Profile                                                                                                                                                                                        |
| H.265+                      | Main stream supports                                                                                                                                                                                |
| Video Bit Rate              | 32 Kbps to 16 Mbps                                                                                                                                                                                  |
| Audio Compression           | G722.1/G.711/G726/MP2L2/PCM/MP3                                                                                                                                                                     |
| Audio Bit Rate              | 64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-192Kbps(MP2L2)/8Kbps-320Kbps(MP3)                                                                                                                    |
| <b>Smart Feature-set</b>    |                                                                                                                                                                                                     |
| Smart Event                 | Line crossing detection, intrusion detection, unattended baggage detection, object removal detection, face detection, scene change detection                                                        |
| Basic Event                 | Motion detection, video tampering alarm, exception (network disconnected, IP address conflict, illegal login, HDD full, HDD error)                                                                  |
| Linkage Method              | Trigger recording: memory card, network storage, pre-record and post-record<br>Trigger captured pictures uploading: FTP, HTTP, NAS, Email<br>Trigger notification: HTTP, ISAPI, alarm output, Email |
| Region of Interest          | Support 1 fixed region for main stream and sub-stream                                                                                                                                               |
| <b>Image</b>                |                                                                                                                                                                                                     |
| Max. Resolution             | 1920 × 1080                                                                                                                                                                                         |
| Main Stream                 | 50Hz: 25fps (1920 × 1080, 1280 × 960, 1280×720)                                                                                                                                                     |


|                               |                                                                                                                                                                                                                                                                                                                                              |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                               | 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280×720)                                                                                                                                                                                                                                                                                              |
| Sub Stream                    | 50Hz: 25fps (640 × 480, 640 × 360, 320 × 240)<br>60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)                                                                                                                                                                                                                                               |
| Third Stream                  | 50Hz: 25fps (1920 × 1080, 1280×720, 640 × 360, 352 × 288)<br>60Hz: 30fps (1920 × 1080, 1280×720, 640 × 360, 352 × 240)                                                                                                                                                                                                                       |
| Image Enhancement             | BLC/3D DNR/HLC                                                                                                                                                                                                                                                                                                                               |
| Image Setting                 | Rotate mode, saturation, brightness, contrast, sharpness, AGC, and white balance adjustable by client software or web browser                                                                                                                                                                                                                |
| Day/Night Switch              | Day/Night/Auto/Schedule/Triggered by Alarm In                                                                                                                                                                                                                                                                                                |
| <b>Network</b>                |                                                                                                                                                                                                                                                                                                                                              |
| Network Storage               | Support Micro SD/SDHC/SDXC card (128G), local storage and NAS (NFS,SMB/CIFS), ANR                                                                                                                                                                                                                                                            |
| Protocols                     | TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour, SSL/TLS                                                                                                                                                                                          |
| General Function              | Anti-flicker, three streams, heartbeat, mirror, privacy masks, password reset via e-mail, pixel counter, HTTP listening                                                                                                                                                                                                                      |
| API                           | ONVIF (PROFILE S, PROFILE G, PROFILE T), ISAPI, SDK                                                                                                                                                                                                                                                                                          |
| Security                      | Password protection, complicated password, HTTPS encryption, 802.1X authentication (EAP-TLS 1.2, EAP-LEAP, EAP-MD5), watermark, IP address filter, basic and digest authentication for HTTP/HTTPS, WSSE and digest authentication for ONVIF, TLS1.2                                                                                          |
| Simultaneous Live View        | Up to 6 channels                                                                                                                                                                                                                                                                                                                             |
| User/Host                     | Up to 32 users<br>3 levels: Administrator, Operator and User                                                                                                                                                                                                                                                                                 |
| Client                        | iVMS-4200, Hik-Connect, Hik-Central                                                                                                                                                                                                                                                                                                          |
| Web Browser                   | Plug-in required live view: IE8+<br>Plug-in free live view: Chrome 57.0+, Firefox 52.0+, Safari 11+<br>Local Service: Chrome 41.0+, Firefox 30.0+                                                                                                                                                                                            |
| <b>Interface</b>              |                                                                                                                                                                                                                                                                                                                                              |
| Audio                         | 1 input (line in, 3.5 mm), 1 output (3.5 mm), mono sound                                                                                                                                                                                                                                                                                     |
| Communication Interface       | 1 RJ45 10M/100M self-adaptive Ethernet port                                                                                                                                                                                                                                                                                                  |
| Alarm                         | 1 input, 1 output (max. 12 VDC, 30 mA), terminal block                                                                                                                                                                                                                                                                                       |
| Video Output                  | 1Vp-p composite output (75 Ω) (For adjustment only)                                                                                                                                                                                                                                                                                          |
| On-board storage              | Built-in Micro SD/SDHC/SDXC slot, up to 128 GB                                                                                                                                                                                                                                                                                               |
| SVC                           | Support H.264 and H.265 encoding                                                                                                                                                                                                                                                                                                             |
| Reset Button                  | Yes                                                                                                                                                                                                                                                                                                                                          |
| <b>Audio</b>                  |                                                                                                                                                                                                                                                                                                                                              |
| Environment Noise Filtering   | Yes                                                                                                                                                                                                                                                                                                                                          |
| Audio Sampling Rate           | 8kHz/16kHz/32kHz/44.1kHz/48kHz                                                                                                                                                                                                                                                                                                               |
| <b>General</b>                |                                                                                                                                                                                                                                                                                                                                              |
| Operating Conditions          | -30 °C to +60 °C (-22 °F to +140 °F), Humidity 95% or less (non-condensing)                                                                                                                                                                                                                                                                  |
| Web Client Language           | 32 languages<br>English, Russian, Estonian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenian, Serbian, Turkish, Korean, Traditional Chinese, Thai, Vietnamese, Japanese, Latvian, Lithuanian, Portuguese (Brazil) |
| Power Supply                  | 12 VDC ± 25%, PoE (802.3at)<br>Terminal block for DC input                                                                                                                                                                                                                                                                                   |
| Power Consumption and Current | 12 VDC, 1.2A, max. 14.5W<br>PoE (802.3at, 42.5V to 57V), 0.5A to 0.1A, max. 16.5W                                                                                                                                                                                                                                                            |
| Protection Level              | IP66, IK10                                                                                                                                                                                                                                                                                                                                   |

|            |                                    |
|------------|------------------------------------|
| Material   | Metal                              |
| Dimensions | Φ144.13×332.73 mm (Φ5.67"× 13.10") |
| Weight     | Camera: Approx. 1890 g (4.17 lb.)  |

## Available Model:

DS-2CD2625FWD-IZS

## Dimensions



## Accessories



DS-1475ZJ-SUS  
Vertical Pole Mount



DS-1476ZJ-SUS  
Corner Mount



DS-1475ZJ-SUS(Black)  
Vertical pole mount



DS-1275ZJ-S-SUS  
Vertical Pole Mount

Distributed by:



## HIKVISION

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310053, China  
T +86-571-8807-5008  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-800-895-0400  
sales.usa@hikvision.com

**Hikvision Italy**  
T +39-0438-69002  
info.it@hikvision.com

**Hikvision Singapore**  
T +65-8884-4718  
sg@hikvision.com

**Hikvision Africa**  
T +27 110 0351172  
sales.africa@hikvision.com

**Hikvision Europe**  
T +31-23-55-48-770  
info.eu@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Oceania**  
T +61-2-8599-4233  
sales.au@hikvision.com

**Hikvision Hong Kong**  
T +852-2151-1761

**Hikvision Middle East**  
T +971-4-8816036  
sales.me@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Canada**  
T +1-800-895-0400  
sales.usa@hikvision.com

**Hikvision Russia**  
T +7-495-869-67-99  
sales.ru@hikvision.com

**Hikvision Poland**  
T +48-22-650-01-50  
poland@hikvision.com

**Hikvision Korea**  
T +82-31-731-8841  
sales.korea@hikvision.com

**Hikvision India**  
T +91-22-29489900  
sales@bomahikvision.com

**Hikvision UK**  
T +01628-902140  
support.uk@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0060  
latam.support@hikvision.com